

SERUM 1000®

ACCELERATOR™

FAST... MOLD STAIN ELIMINATOR

THE SOURCE FOR REMEDIATION SOLUTIONS

DESCRIPTION:

Serum 1000 Accelerator is a designed additive to cause Serum 1000 to perform at a higher level than the Serum 1000 by itself. Serum 1000 for years has performed flawlessly at cleaning all organics and bleaching some of the organic stains that mold leaves behind. The Accelerator is designed to cause Serum 1000 to create billions of hydroxyl radicals to super charge it's bleaching qualities. Now with the Accelerator, you can clean the organics faster because of it's super excited state and be assured that all the staining will be bleached away improving the esthetics of all surfaces being cleaned.

The Accelerator is packaged as 15 ounces in a quart bottle which is what is required to accelerate five (5) gallons of Serum 1000. If less accelerated product is desired, you may measure and add three (3) ounces of Accelerator per each gallon of Serum 1000 that you would like to treat and accelerate.

Shelf life of Accelerated Serum 1000 is approximately one and one half to two days. (1.5-2 days). Any run off from spraying accelerated Serum 1000 that may occur is pH 9. The only by product of the accelerated Serum 1000 is water, oxygen and potassium acetate (a food additive).

INSTRUCTIONS:

DO NOT MIX THE ACCELERATOR UNTIL YOU ARE READY TO SPRAY. Remove cap from 5 gallon pail of Serum 1000. Pour entire contents of this bottle (Serum 1000 Accelerator) into the 5 gallon pail of Serum 1000. Place the Airless Sprayer pickup tube into the 5 gallon pail of Serum 1000 just treated with the Serum 1000 Accelerator. Spray the accelerated Serum 1000 on all surfaces in the contained area as normal. Use a stiff bristle deck brush to agitate areas of thick visible mold or heavy dark spots while spraying those areas with accelerated Serum 1000. You should experience profuse foaming from areas of living organisms. Re-spray foaming areas after about 10 minutes. If no more foaming, that area is completed. If it foams again, re-spray with the accelerated Serum 1000 until foaming stops. Wait at least one hour for surfaces to dry, then HEPA vacuum all surfaces in the contained area.

The bottle of Serum 1000 Accelerator will treat 5 gallons of Serum 1000. If less than 5 gallons needs to be treated, measure 3 ounces of Accelerator per each gallon of Serum 1000 to be treated. Do not over treat each gallon of Serum 1000 or extreme foaming will occur in the Serum 1000 being treated. Three (3) ounces only of the Accelerator per gallon of Serum 1000. If treated Serum 1000 is left in the pail, DO NOT SCREW THE CAP ON TIGHT. PLEASE LEAVE ENOUGH THREADS SO THE CAP WILL VENT THE OXYGEN GAS OFF FROM THE SOLUTION INSIDE.

CAUTIONS:

USE EXTREME CAUTION WHILE POURING THE ACCELERATOR INTO THE 5 GALLON PAIL. USE EYE PROTECTION AND CHEMICAL RESISTANT GLOVES WHILE HANDLING THIS PRODUCT. Contains Potassium Hydroxide. Do not get on skin. *If spilled on clothing*, immediately remove the clothing. Do not re-wear clothing until after washing. *If skin contact occurs*, rinse contact area for at least 5 minutes with potable water then treat area of contact with a mild solution of vinegar then wash thoroughly with soap and water. *If eye contact occurs*, flush with copious amounts of potable water while transporting to medical assistance. *If ingestion occurs*, DO NOT INDUCE VOMITING. Give large amounts of potable water while seeking emergency medical assistance.

Serum Products, LLC

1355-B West Oak Commons Lane, Marietta, Ga. 30062

Local (678) 290-1880 • (678) 290-1769 Fax

Toll Free (866) 477-6078



PRODUCT PART # 5-730-12

DESCRIPCIÓN:

Suero 1000 Accelerator es un aditivo diseñado para causar Suero 1000 para llevar a cabo a un nivel más alto que el suero 1000 por sí mismo. Suero 1000 para años ha realizado sin problemas en la limpieza de todos los compuestos orgánicos y blanquear algunas de las manchas orgánicas que deja tras de molde. El acelerador está diseñado para causar Serum 1000 para crear miles de millones de radicales hidroxilo a carga estupenda que está blanqueando cualidades. Ahora, con el acelerador, se puede limpiar los materiales orgánicos más rápido debido a su estado súper emocionada y estar seguro de que toda la tinción se blanquea mejorar la estética de distancia de todas las superficies a limpiar.

El acelerador se empaqueta como de 15 onzas en una botella de un cuarto, que es lo que se requiere para acelerar los cinco (5) galones de Suero 1000. Si se desea producto menos acelerado, es posible medir y agregar tres (3) onzas de acelerador por cada galón de suero 1000 que desea tratar y acelerar.

La vida útil de Accelerated Serum 1000 es de aproximadamente una hora y media a dos días. (1.5-2 días). Cualquier escurrimiento de pulverización acelerado Suero 1000 que puede ocurrir es de pH 9. El único subproducto de la Suero acelerado 1000 es el agua, el oxígeno y acetato de potasio (aditivo alimentario).

INSTRUCCIONES:

NO MEZCLAR EL ACELERADOR hasta que esté listo para aplicar. Quite la tapa del balde de 5 galones de Suero 1000. Vierta todo el contenido de esta botella de suero (1000) Acelerador en el cubo de 5 galones de Suero 1000. Coloque el tubo de toma Rociador sin aire en el cubo de 5 galones de Suero 1000 sólo tratados con el suero 1000 Accelerator. Rocíe el suero acelerado 1000 en todas las superficies en el área contenida de forma normal. Use un cepillo de cerdas duras cubierta para agitar las áreas de moho visible grueso o manchas oscuras pesadas mientras se pulveriza aquellas áreas con acelerada Serum 1000. Usted debe experimentar la formación de espuma abundante de las áreas de los organismos vivos. Re-aerosol espumante áreas después de unos 10 minutos. Si no hay más formación de espuma, se completa esa zona. Si hace espuma de nuevo, volver a pulverizar con el Serum acelerado 1000 hasta obtener espuma paradas. Espere al menos una hora para que las superficies se sequen, luego use la aspiradora HEPA todas las superficies en el área contenida.

La botella de suero 1000 Acelerador tratar 5 galones de Suero 1000. Si es menos de 5 galones necesita ser tratada, mida 3 onzas de acelerador por cada galón de suero 1000 a tratar. No más de tratar cada galón de suero 1000 o formación de espuma extrema se producirá en el suero 1000 que está siendo tratado. Tres (3) onzas sólo del acelerador por galón de suero 1000. Si Serum tratado 1000 se deja en el cubo, **NO** cierre la tapa apretada. **POR FAVOR DEJE DE ROSCA** suficiente para que el PAC deberá ventilar el gas oxígeno de la disolución INTERIOR.

PRECAUCIONES:

Tenga mucho cuidado cuando **COLADA DEL ACELERADOR EN EL CUBO 5 LITROS. USE PROTECCIÓN OCULAR Y Guantes** resistentes a químicos durante la manipulación de este producto. Contiene hidróxido de potasio. No lo ponga sobre la piel. Si se derrama en la ropa, retire inmediatamente la ropa. No volver-ware ropa hasta después del lavado. Si se produce contacto con la piel, lave el área de contacto durante al menos 5 minutos con agua potable y luego tratar la zona de contacto con una solución suave de vinagre después lávese bien con agua y jabón. Si se produce contacto con los ojos, lave con abundante cantidad de agua potable, mientras que el transporte de la asistencia médica. Si se produce la ingestión, **NO** induzca el vómito. Beber gran cantidad de agua potable, mientras que la búsqueda de asistencia médica de emergencia.

CAUTIONS

Keep out of the reach of children. Do not ingest. When not in use, keep container closed using the original pail VENTED cap. Do not dispose of unused portions into water ways, creeks, rivers, estuaries or oceans. Do not reuse empty container. Proper **Personal Protection Equipment (PPE)**: use full face mask with filter cartridges such as 3M 60926 or equivalent, full body protection suit with head and foot covers, chemical resistant gloves and boots, tape at the wrist over suit and gloves to prevent unwanted exposure to the product. Change air filter cartridges at manufacturers recommended frequency. Discard body suit after one use. **DO NOT REUSE BODY SUIT**



Our **Serum System** was used on **Extreme Make Over - Home Edition** March 11, 2007 on a house in Lake Arrowhead, Ga.

The newly constructed house stood for over 14 months unfinished because of family tragedy.

The front foundation did not have a french drain to divert water. Water ran under the front footing and was trapped in the crawl space by the back foundation wall. There was no vents in the foundation to exhaust the moisture. Moisture intruded from the sides and top of the structure as well.

As a result of these conditions, the crawl space was full of water and that contributed to a high moisture level to the interior of the house. The roof only had plywood sheeting with no tar paper. The house has two 2700 sq. ft. two stories with bonus rooms in the cathedral ceiling and a 2700 sq. ft. crawl space. Total area for remediation about 42,400 sq. ft. of sprayable area and only 24 hours to accomplish the job! The job was finished in less than 21 hours with no return of unsightly stains or objectionable odors. Oh and the house was totally uncontained the entire time during cleaning and testing!!! The house had no windows or doors.

We passed clearance testing with a 99.9% reduction in organic mass.

Serum Products, LLC

1355-B West Oak Commons Lane, Marietta, Ga. 30062

Local (678) 290-1880 • (678) 290-1769 Fax

Toll Free (866) 477-6708