



SERUM TG-HD

Tile & Grout Cleaner

Acid pH (less than 1)
Aggressive Cleaner, Free Rinses with Cold Water
Removes Body Oils and Enhances Gloss on Tile
Deep Cleans and Brightens Grout
Biodegradable

Where to Use

Designed for heavy duty cleaning of severely dirty Tile and Grout and Concrete. Using a pump up or trigger sprayer, apply to severely soiled Tile and Grout, allow to dwell, using a stiff brush, agitate the Tile and Grout area, rinse with clean water.

If odors are present, they may be coming from the Grout lines where urine or other organics may have penetrated and are now wicking up. Using Serum SBC, spray liberally on the Grout lines, allow to seep into the Grout lines and allow to dwell 15 minutes. Rinse with clean water. This will eliminate the odor completely.

If using a spinner tool, apply Serum TG-HD, after appropriate dwell time, agitate per manufactures directions, rinse, and vacuum excess material to the waste tank.

Concrete Cleaning where environmental stains are present. Dilute to necessary strength after testing surface. Apply with a pump up sprayer and let dwell 15 minutes. Using either a soft wash spinner tool or a pressure washing wand, rinse with clean water.

**DO NOT USE ON NATURAL STONE AS IT WILL ETCH...
DO NOT USE DIRECTLY ON ALUMINUM AS IT WILL DISCOLOR THE MATERIAL...**

Safe Handling and PPE Safety Cautions:

Serum SBC is an Oxidizer. Glasses and Gloves are required for use. Tile and Grout is an acidic cleaner with a pH of less than 1. Use Glasses and Chemical resistant Gloves for safe handling. Knee pads are recommended when working on tile floors to both protect your knees from contact with the cleaner.

Do not spray into electrical outlets and care should be taken to contain/protect all electrical switches, junction boxes and electrical equipment. It is recommended to guard against overspray when spraying around CPVC fire suppression pipe and proper draping and containment should be done.

Avoid Contact with skin. Do not ingest. Keep out of the reach of children.

PPE Requirements on The Job:

Water resistant to waterproof full body Tyvek or like suits with booties and hood. Should be properly sized and worn to manufactures specifications. Chemical resistant gloves, full facial protection with P-100 AG (acid-gas) OV (organic-vapor) Yellow/Magenta cartridges installed, used, and changed to manufactures specifications.

Properties

Shelf Life: Guaranteed 1 Year from Date of Purchase

Minimum Application Temp: 40° F

Maximum Application Temp: 95° F

Drying times: Rinse and Air Dry

